



ROYCE THOMPSON
LIGHTING TECHNOLOGY IN CONTROL

miscellaneous lighting controls

miscellaneous lighting controls



A RANGE OF LIGHTING CONTROLS FOR A WIDE VARIETY OF APPLICATIONS, ALL MANUFACTURED TO THE SAME HIGH STANDARD AS OTHER ROYCE THOMPSON PRODUCTS.

V4 Range Photocell



Sensor	Cadmium Sulphide
Switching Level	V4A:25-2000 Lux
	V4O3:25-50,000 Lux
Switching Differential	1:1.5
Voltage	230v-6% + 10% 50Hz
Max Lamp Load	3x400w HPS
Max Resistive Load	8A
Power Consumption	<0.5W
Ingress Protection	IP65
Warranty	2 years

ROTO FLASH Controller for flashing beacons / signs



Voltage	240v +/- 6% 50Hz
Flash Rate	48 / min (std)
Rating	500 w (max)
Energy Consumption	1.5W
Warranty	2 years

V16



Sensor	Cadmium Sulphide
Switching Level	5 - 1000 LUX
Switching Differential	1:1.5
Voltage	230v-6% + 10% 50Hz
Max Inductive Load	2200 VA
Max Resistive Load	10A
Switching Delay	10 Secs on 40 Secs off
Ingress Protection	IP54
Warranty	2 years

Astro Log Astronomic time switch for lighting control



Voltage	240v-6% +/- 10% 50Hz
Switching Capacity (resistive)	16A
Switching Capacity (inductive)	10A
Power Consumption	6VA
Accuracy	Better than 1 second per day
Warranty	2 years
Features	4 year battery backup Automatic GMT/BST time change Part night capability
	Dusk/dawn offset upto 99 mins Factory set astronomic programme Automatically accounts for leap year

Royce Thompson products are fully RoHS compliant.

ACE BUSINESS PARK, MACKADOWN LANE, KITTS GREEN, BIRMINGHAM B33 0LD
TELEPHONE 0121 785 4700 FAX 0121 785 4717
EMAIL: SALES@ROYCETHOMPSON.COM WWW.ROYCETHOMPSON.COM



Certificate No: FM13065

